

SYBEX Index

SilverFast[®]: The Official Guide

Taz Tally, Ph.D.

Index

Copyright © 2003 SYBEX Inc., 1151 Marina Village Parkway, Alameda, CA 94501. World rights reserved. No part of this publication may be stored in a retrieval system, transmitted, or reproduced in any way, including but not limited to photocopy, photograph, magnetic or other record, without the prior agreement and written permission of the publisher.

ISBN: 0-7821-4197-8

SYBEX and the SYBEX logo are either registered trademarks or trademarks of SYBEX Inc. in the USA and other countries.

TRADEMARKS: Sybex has attempted throughout this book to distinguish proprietary trademarks from descriptive terms by following the capitalization style used by the manufacturer. Copyrights and trademarks of all products and services listed or described herein are property of their respective owners and companies. All rules and laws pertaining to said copyrights and trademarks are inferred.

This document may contain images, text, trademarks, logos, and/or other material owned by third parties. All rights reserved. Such material may not be copied, distributed, transmitted, or stored without the express, prior, written consent of the owner.

The author and publisher have made their best efforts to prepare this book, and the content is based upon final release software whenever possible. Portions of the manuscript may be based upon pre-release versions supplied by software manufacturers. The author and the publisher make no representation or warranties of any kind with regard to the completeness or accuracy of the contents herein and accept no liability of any kind including but not limited to performance, merchantability, fitness for any particular purpose, or any losses or damages of any kind caused or alleged to be caused directly or indirectly from this book.

Sybex Inc.
1151 Marina Village Parkway
Alameda, CA 94501
U.S.A.
Phone: 510-523-8233
www.sybex.com

Index

Note to the Reader: Throughout this index **boldfaced** page numbers indicate primary discussions of a topic. *Italicized* page numbers indicate illustrations.

-
- A**
- Abs. Colorimetric option, 171
 - accessing
 - DC-VLT images, 187
 - ICC profiles, 165, 166
 - PhotoCD image libraries, 189
 - acquiring
 - ICC profiles, 165, 166
 - images, 38–39. *See also*
 - automatic scanning; manual scanning
 - ACR (Adaptive Color Restoration) tool, 102–103, 103
 - activating
 - HDR tool, 181, 181
 - scan frames, 152
 - ADCs (analog-to-digital converters), 25–26
 - Add Preview button, 159
 - Add Single Image From Film Strip button, 158
 - additive color, 14
 - Adjust Image Automatically option, 159
 - Adobe Color Engine CMM, 162
 - AdobeRGB1998 profile, 168
 - albums, 187–188, 189
 - analog-to-digital converters (ADCs), 25–26
 - Apple Macintosh system
 - requirements, 32
 - archiving images, 174
 - Ask Jeeves search engine, 40
 - auto-adjustment options
 - Auto Contrast, 52, 53
 - Auto Frame Inset, 51
 - Auto Threshold Highlight and Shadows, 49–50, 51
 - AutoPip Middle Factor, 51–52
 - Color Cast Removal, 51
 - Highlight Offset and Shadow Offset, 50
 - MidPip Fixed Target, 52
 - Scan Control window, 48–49, 49
 - scan type, 47–48
 - auto-adjustment tools, 46–47
 - applying, 52
 - for complex color line art, 144, 144
 - for manual scanning, 62, 63
 - results of, 69
 - Auto Contrast setting, 52, 53
 - Auto Frame Inset setting, 51
 - Auto Sharpen option, 116
 - Auto tab, 49, 49
 - Auto Threshold Highlight setting, 49–50, 51
 - Auto Threshold Shadows setting, 49–50, 51
 - auto unsharp masks, 115–116
 - Automatic option for color, 166
 - automatic scanning, 41
 - calibration for, 42–45, 43, 45
 - completing, 58
 - prescans for. *See* prescans scanner and image preparation for, 42
 - AutoPip Middle Factor setting, 51–52
-
- B**
- background removal in complex line art, 139, 139
 - batch scanning, 154
 - bit depth, 5, 8
 - and channels, 6–8, 7
 - for complex line art, 137
 - bitmap images
 - in line art, 134, 134
 - pixels in, 27
 - vs. vector images, 2
 - for drawing applications, 2–3, 2–3
 - for painting programs, 3–4, 3
 - bitmap mode, 13
-
- C**
- bits
 - in grayscale mode, 13
 - for pixel values, 3–4, 3
 - brightness, 76–79, 76, 79–80
 - Brightness tool, 77–79
 - bytes
 - in grayscale mode, 13
 - for pixel values, 3–4, 3
-
- C**
- Calibrated auto-adjustment tool, 47
 - calibration, 42–43
 - frequency of, 45
 - IT8 target for, 34, 43–45, 43, 45
 - Calibration option for color, 165–166
 - capturing. *See* scanning
 - CCD scanners
 - configurations for, 26–27, 27
 - operation of, 24–26, 25–26
 - CCDs (charge coupled devices), 23
 - channels, 6–8, 7
 - CIELab mode, 17
 - CIELab option for output, 167
 - clean scans for sharpening, 120
 - cleaning scanner surfaces, 42
 - CMMs (color management modules), 162, 164, 164
 - CMS tab, 165, 166
 - Color Management pane, 165–167
 - Embedded ICC Profiles pane, 171, 172
 - exiting, 173, 174
 - Plug & Play CMYK pane, 172–173, 173
 - profile setup comparison, 171, 171
 - Profiles For ColorSync pane, 167–171, 168, 170–171
 - CMYK color (four-channel) images, 7, 7

- CMYK color space, 162–163
- CMYK mode, 15–16, 15–16
- color, 13, 87
 - adding, 99, 100
 - bit depth for, 5
 - color balance, 79
 - color curves for, 82–84, 83–84
 - Global Color Correction tool for, 80–82, 81–82
 - for highlights, 82
 - image results, 83, 85
 - across tonal range, 81–82, 82
 - color casts
 - histograms for, 73–74, 73
 - removing, 74–76, 75
 - saving, 74–75
 - color gamuts, 14, 163, 163
 - curves for
 - for color balance, 82–84, 83–84
 - for color correction, 92–95, 93–95
 - densitometers for, 64, 88–92, 88–92
 - in line art, 140–141
 - complex, 143–146, 144–147
 - simple, 141–143, 142–143
 - managing, 161–162
 - color gamuts in, 163, 163
 - color spaces in, 162–163
 - ICC profiles for. *See* CMS tab; ICC profiles
 - output tips for, 174–177
 - workflows in, 174, 175
 - matrix sets for, 97–98, 99
 - MidPip tool for, 95–96, 97
 - modes for
 - CMYK, 15–16, 15–16
 - Indexed Color, 17–18, 18
 - Lab, 16–17, 16–17
 - monochrome, 13, 14
 - RGB, 14
 - numbers for, 88, 98
 - preset adjustments for, 99–100, 100
 - restoration of, 102–103, 103
 - saturation of, 99, 99
 - selecting
 - for adjustments, 97–98
 - through masking, 100–101, 100, 102
- Color Cast Removal setting, 51
- Color channel mode selector, 77
- Color LCD profile, 168
- Color-managed auto-adjustment tool, 47
- color management modules (CMMs), 162, 164, 164
- Color Management pane, 165–167, 166
- Color Settings dialog box, 169
- color spaces, 162–163
- ColorMatch profile, 168
- Colormodel setting, 60
- ColorSync CMM, 162
- ColorSync option
 - for color, 166
 - for monitors, 166
 - for output, 167
- combined histogram mode, 66
- commercial printing, 176
- complex line art, 136
 - color, 143–146, 144–147
 - finishing scan for, 139
 - histogram analysis for, 137–139, 138–139
 - setup and prescan for, 136–137
- compression
 - in Expert Dialog, 111
 - JPEG, 19–20
- contrast
 - controlling, 78, 79–80
 - overall, 96
 - in sharpening, 114–115, 114
- Contrast control, 77
- converting light into digital signals, 22–23, 22–23
- copying scan frame
 - characteristics, 153
- curves
 - for color, 92–93, 93
 - for adjustments, 94–95, 95
 - for balance, 82–84, 83–84
 - for histogram corrections, 94, 94–95
 - for image evaluation, 93–94, 93–94
 - for complex color line art, 146, 146–147
 - in Expert Dialog, 107–108, 107
 - custom profiles, 164
 - customizing ScanPilot, 150–151, 151
- Dark Contour setting, 119
- data sections in Expert Dialog, 108–110, 108–111
- DC version, 185
- DC-VLT (Digital Camera Virtual Light Table) version, 186–188, 187, 189
- Default Setting, 60
- defaults, ScanPilot, 150, 150
- Defaults window, 49, 49
 - CMS tab. *See* CMS tab
 - for manual scanning, 60–62, 62
- Defect Size setting, 128
- Defect Type setting, 128
- deleting
 - job entries, 155
 - scan frames, 153
- Densitometer Radius setting, 60
- Densitometer window, 35
- densitometers, 64–65, 64
 - for color numbers, 88
 - for fixed-PIP points, 88–89, 88–89
 - for grayscale, 8, 9, 64
 - histograms for, 89–91, 89, 91
 - for image adjustments and tracking numbers, 90, 90
 - raw measurements for, 89–90, 89
 - for skin tone, 91–92, 92
- Descreening control window, 121–122, 121
- descreening process, 121–123, 121–124
- Design Tools Monthly, 40
- desktop printing, 176
- detailed line art, 136
 - color, 143–146, 144–147
 - finishing scan for, 139
 - histogram analysis for, 137–139, 138–139
 - setup and prescan for, 136–137
- Detection setting in SRD, 128
- device profiles, 164
- Device settings, 36
- diffuse highlights, 5
- Digital Camera Virtual Light Table (DC-VLT) version, 186–188, 187, 189
- digital signals, converting light into, 22–23, 22–23

digitization, 21
 dpi (dots per inch), 9–11
 dpi/dpcm button, 55
 dpi setting, 38
 dpi slider, 38
 drawing applications, 2–3, 2–3
 drum scanners, 23–24, 24
 duplicating scan frames, 152
 dust, SRD for, 126–131, 127,
 129–131
 dynamic range of drum scanners, 24

E
 e-mail, images for, 176
 edges
 in line art. *See* line art
 in sharpening, 114–115, 114
 editing
 color curves, 84
 Expert Dialog, 111
 HDR images, 183–185, 184–185
 job entries, 156, 156
 PhotoCD images, 190
 effective scan resolution, 56
 8-bit grayscale images, 6, 7
 Embedded ICC Profiles pane,
 171, 172
 EPS file format, 19–20
 evaluating images, 68
 Expert Dialog, 105
 columns in, 106–107, 107
 data sections in, 108–110,
 108–111
 editing, 111
 graph display in, 107–108, 107
 ramps in, 111
 saving changes in, 112, 112
 values in, 106, 107
 Expert tool, 63, 63
 exporting data, 112

F
 Factors tab, 185, 185
 file formats
 for job images, 157
 for print and Internet, 19–20,
 19–20
 filmstrips, scanning, 158–159, 159
 Filter menu for USMs, 116
 Filter setting, 37, 53
 FireWire cables, 32–33

fixed-PIP points, 88–89, 88–89
 flatbed scanners, 24–26, 25
 For HDR (High Dynamic Range)
 Output option, 61
 four-channel (32-bit CMYK color)
 images, 7, 7
 14 -> 8 Bit Grayscale scan type
 setting, 47
 42 -> 24 Bit Color scan type
 setting, 47
 48 Bit Color scan type setting, 48
 48 Bit HDR color scan type
 setting, 48
 Frame-Set setting, 36
 Frame-sets, 153
 Frame tab
 options in, 37–38, 37–38
 for prescans, 52–58, 55, 57
 for scan frames, 151

G
 Gamma-Gradation setting, 61
 gamuts, 14, 163, 163
 GANE control window, 124, 125
 GANE (Grain And Noise
 Elimination) technology,
 124–126, 125–127
 General tab
 for manual scanning, 60–62, 62
 in Scan Control window, 36, 37
 generic profiles, 164
 GIF file format, 20
 Global Color Correction tool, 63, 63,
 80–82, 81–82
 Google search engine, 40
 Gradation Curves tool, 63, 63
 for brightness, 76–77, 76
 for color, 92–93
 adjustments, 94–95, 95
 for complex line art, 146, 146
 for histogram corrections,
 94, 94–95
 for image evaluation, 93–94,
 93–94
 presets for, 53
 gradient data in Expert Dialog,
 108, 108
 Grain And Noise Elimination
 (GANE) technology, 124–126,
 125–127
 graph display in Expert Dialog,
 107–108, 107

Gray Matrix 6 tab, 185, 185
 Gray profile, 169
 grayscale mode, 4, 13, 14
 grayscale values, 8–9, 9
 bit depth for, 5
 densitometer for, 64

H
 hard drive space requirements, 32
 HDR Scan Control window, 181, 181
 HDR tool
 activating, 181, 181
 adjusting images in, 183–185,
 184–185
 capturing images in, 180
 opening images in, 182–183
 help
 in ScanPilot, 34, 150
 sources for, 40
 Help Text window, 34
 Helptexts option, 150
 high-contrast edges in sharpening,
 114–115, 114
 High Resolution Prescan setting, 61
 Highlight control, 77
 Highlight Offset setting, 50
 highlight tonal areas, 4–5, 4
 Highlight tool, 63, 63, 69–70, 69–70
 highlights, 5
 color balance for, 82
 for complex line art
 color, 144, 144
 in histograms, 138, 138
 in Expert Dialog, 108,
 109–110, 110
 fine-tuning, 78
 histograms for, 71–73, 72–73
 settings for, 68–73, 69–73
 HiRepp tool, 183
 Histogram tool, 63, 63
 histograms, 66–67, 67
 for color cast corrections,
 73–74, 73
 for complex line art
 color, 144–146, 145
 grayscale, 137–139, 138–139
 for densitometer points, 89–91,
 89, 91
 Gradation Curves tool for, 94,
 94–95
 for highlight and shadow
 correction, 71–73, 72–73

presets for, 53
 for simple color line art,
 141–142, 142–143
 for tonal data, 4, 5
 values in, 90
 horizontal tools palette, 62, 63

ICC (International Color Consortium), 162
 ICC color management, 162
 ICC profiles
 acquiring and accessing, 165, 166
 CMS tab for. *See* CMS tab
 creating, 164–165
 ICM option
 for color, 166
 for monitors, 166
 for output, 167
 IEEE 1394 cables, 32–33
 Image resolution setting, 54
 Image Type menu, 37, 37, 53
 images
 acquiring and saving, 38–39. *See*
also automatic scanning;
 manual scanning
 channels for, 6–8, 7
 dimension and quality of,
 11–13, 12
 information tools for, 64
 densitometers, 64–65, 64,
 90, 90
 histograms, 66–67, 67
 Show Lightest And Darkest
 Points tool, 67–68, 68
 Indexed Color mode, 17–18, 18
 input resolution vs. output
 resolution, 9–11, 10
 Intensity setting
 in GANE, 125–126
 in SRD, 128
 for USMs, 117
 Internal setting, 168, 168
 Internal -> Monitor setting, 166
 Internal -> Output setting, 167
 International Color Consortium
 (ICC), 162
 Internet, file formats for, 19–20,
 19–20
 interpolated scanner resolution,
 27–28

Interpolation setting, 61
 IT8 Calibration dialog box,
 164–165, 165
 IT8 target, 34, 43–45, 43, 45

Job Manager, 154
 activating scanning process,
 157–158
 creating and deleting job
 entries, 155
 editing job entries, 156, 156
 final job prep, 157
 saving and loading jobs, 156
 scanning filmstrips with,
 158–159, 159
 starting, 155, 155
 JPEG file format, 19–20

Lab mode, 16–17, 16–17
 LaserSoft Imaging help, 40
 LEDs (light emitting diodes), 25
 Lempel-Ziv-Welch (LZW)
 compression, 20
 Less Auto Sharpen option, 116
 Levels options, 49–50, 51
 light, converting into digital signals,
 22–23, 22–23
 Light Contour setting, 119
 light emitting diodes (LEDs), 25
 lightness, 16
 line art, 13–14, 14, 133
 color in, 140–141
 complex, 136
 color, 143–146, 144–147
 finishing scan for, 139
 histogram analysis for,
 137–139, 138–139
 setup and prescan for,
 136–137
 pixels and vectors in, 134, 134
 simple
 color, 141–143, 142–143
 scanning, 135–136, 136
 lines per inch (lpi), 11
 loading jobs, 156
 locked output options, 54
 Longish Scratch Removal pane, 130
 lossy compression, 19–20

lpi (lines per inch), 11
 lpi/lpcm setting, 38, 55
 LZW (Lempel-Ziv-Welch)
 compression, 20

Magnifier menu, 188
 manual scanning, 59
 brightness settings, 76–79, 76,
 79–80
 color balance settings, 79–84,
 81–85
 color cast settings, 73–76, 75
 contrast settings, 78, 79–80
 General tab for, 60–62, 62
 highlights and shadows settings,
 68–73, 69–73
 image information tools for,
 64–68, 64, 67–68
 scanning tools for, 62–64, 63
 manual unsharp masks, 116–118, 116
 Mask Edge Size setting, 62
 masks
 selections through, 100–101,
 100, 102
 for SRD, 129–130, 130
 unsharp. *See* unsharp masks
 (USMs)
 matrix sets, 97–98, 99
 Matrix setting, 117
 Max setting, 108, 109
 MByte setting, 38, 54
 measurement modes in
 densitometer, 65
 memory requirements, 32
 middle value in Expert Dialog,
 110, 110
 MidPip Fixed Target setting, 52
 MidPip tool, 63
 for color, 95–96, 97
 in Expert Dialog, 110
 Midtone adjustment tool, 77
 midtone areas, 4, 4
 Min setting, 108, 109
 model profiles, 164
 moire patterns, 121
 monochrome modes, 13
 More Auto Sharpen option, 116
 Motive dialog box, 53, 54
 moving scan frames, 152
 multiple scan frames, 152–153, 153
 multipurpose images, 177

-
- Name New Frame dialog box, 151
 Name setting, 38, 57
 NegaFix dialog box, 158
 Next Image option, 190
 None option
 for color, 165
 for monitors, 166
 NTSC1953 profile, 169
 numbers for color, 88, 98
-
- N** pixels, 2
 in bitmap images, 27
 in line art, 134, 134
 representation of, 3–4, 3
 in resolution, 9
 pixels per inch (ppi), 9
 Plug & Play CMYK pane,
 172–173, 173
 plug-ins, 34
 PMT (photomultiplier tube)
 scanners, 23–24, 24
 PNG file format, 20
 Pos./Neg. setting, 36
 power user tools, 149
-
- O** batch scanning, 154
 Job Manager, 154–159, 155–159
 scan frames, 151–153, 152–153
 ScanPilot, 150–151, 150–152
 PowerPoint presentations, 176–177
 P&P CMYK option, 167
 ppi (pixels per inch), 9
 prescan images, scanning. *See*
 manual scanning
 Prescan window, 35, 38–39
 prescans, 45–46
 auto-adjustment options for,
 47–52, 49, 51, 53
 auto-adjustment tools for,
 46–47, 52
 Frame tab settings for, 52–58,
 55, 57
 for line art
 complex, 136–137,
 143–144, 144
 simple, 141
 presentation applications, 176–177
 previews in SRD, 128
 Previous Image option, 190
 printed images, 121
 descreening process for,
 121–123, 121–124
 file formats for, 19–20, 19–20
 GANE for, 124–126, 125–127
 SRD for, 126–131, 127, 129–131
 printing thumbnail sheets, 190
 process color, 16
 processor requirements, 32
 Profile Warning window, 173, 174
 profiles
 acquiring and accessing, 165, 166
 CMS tab for. *See* CMS tab
 creating, 164–165
-
- P** painting programs, 3–4, 3
 PAL_SECAM profile, 169
 pausing jobs, 157
 PDF files, 177
 Perceptual option, 170
 PhotoCD Folder option, 190
 PhotoCD Open Image option, 190
 PhotoCD Overview option, 190
 PhotoCD version, 188–190
 photomultiplier tube (PMT)
 scanners, 23–24, 24
 Photoshop
 profile matching in, 169
 for scanning, 46
 photosites, 25
 pixel bricks, 6
 Pixel Lock icon, 56
-
- Profiles For ColorSync pane,
 167–171, 168, 170–171
 proportional adjustments, 54
 PSD file format, 19–20
-
- Q** Q-Factor setting, 38, 55, 61
 quality and resolution, 11–13, 12
 quality factor, 13
 quarter tone areas, 4, 4
 Quick Start Guide, 40
-
- R** radius checks in densitometer, 65
 Radius setting for GANE, 125–126
 RAM requirements, 32
 ramps in Expert Dialog, 111
 raw measurements for densitometer
 points, 89–90, 89
 Realtime Correction option, 62
 recalling scan frames, 152–153
 Rel. Colorimetric option, 170
 removing color casts, 74–76, 75
 Rendering Intent settings, 170
 Reopen SF After Scan option, 61
 resetting job status, 158
 resolution, 9
 effective, 56
 input vs. output, 9–11, 10
 in line art, 135–136
 optical vs. interpolated, 27–28, 29
 and quality, 11–13, 12
 Resolution field setting, 55
 resolution slider, 55
 restoration of color, 102–103, 103
 reversed curves in Expert Dialog,
 107–108
 RGB color (three-channel) images,
 6, 7
 RGB color space, 162–163
 RGB mode, 14
 RGB output option, 167
-
- S** saturation of color, 99, 99
 Saturation output option, 171
 Save Settings menu, 77
 Save window, 112, 112

- saving
 - color casts, 74–75
 - Expert Dialog changes, 112, 112
 - images, 38–39
 - jobs, 156
 - scan frames, 151, 153
 - SRD settings, 131
 - SC2G tool, 183–184, 184–186
 - Scale % setting, 38, 54
 - scaling in line art, 135–136, 139–140, 143
 - Scan Batch button, 154
 - Scan Control window, 35
 - auto-adjustment options for, 48–49, 49
 - Frame tab, 37–38, 37–38
 - General tab, 36, 37
 - scan frames, 151–153, 152–153
 - Scan Mode setting, 36
 - Scan Pilot, 58
 - Scan RGB button, 154
 - Scan Type setting, 37
 - scanned images, 1
 - bit depth in, 5
 - bitmap vs. vector, 2–4, 2–3
 - color for, 13–18, 14–18
 - file formats for, 19–20, 19–20
 - folders for, 157
 - grayscale for, 8–9, 9
 - image channels for, 6–8, 7
 - parts of, 4–5, 4
 - resolution of, 9–13, 10, 12
 - Scanner -> Internal setting, 165–166
 - Scanner (Reflective) setting, 168
 - Scanner (Transparent) setting, 168
 - scanners, 21
 - CCD, 24–26, 25–26
 - configurations for, 26–27, 27
 - converting light into digital signals, 22–23, 22–23
 - PMT, 23–24, 24
 - preparing, 42
 - resolution of, 27–29, 29
 - scanning
 - automatic. *See* automatic scanning
 - filmstrips, 158–159, 159
 - HDR images, 180
 - manual. *See* manual scanning
 - ScanPilot tool, 150
 - customizing, 150–151, 151
 - default, 150, 150
 - Help Text window for, 34
 - ScanPilot window, 35
 - Scratch Disk setting, 61
 - scratches, SRD for, 126–131, 127, 129–131
 - Screen menu, 122, 122
 - screen patterns, 121
 - Screen setting, 38, 55
 - SCSI (Small Computer System Interface) cables, 32–33
 - selecting
 - color
 - for adjustments, 97–98
 - through masking, 100–101, 100, 102
 - PhotoCD images, 189
 - Selective Color Correction tool, 63, 63, 97, 97
 - for adding colors, 99, 100
 - for color matrix sets, 97–98, 99
 - masking for, 100–101, 100, 102
 - preset adjustments for, 99–100, 100
 - for restoration, 102–103, 103
 - for saturation, 99, 99
 - Selective Color tool, 184, 185
 - Separated histogram mode, 66
 - Setting menu, 37
 - Settings option, 56
 - setup for color line art
 - complex, 136–137, 143–144, 144
 - simple, 141
 - shades of gray, 5
 - shadow areas, 4, 4
 - Shadow control, 77
 - Shadow Offset setting, 50
 - Shadow Soft option, 119
 - Shadow tool, 63, 63, 69–70, 69–70
 - shadows
 - for complex line art
 - color, 144, 144
 - grayscale, 138, 138
 - in Expert Dialog, 108, 109–110, 110
 - fine-tuning, 78
 - histograms for, 71–73, 72–73
 - settings for, 68–73, 69–73
 - Sharpen (USM) dialog box, 118–119
 - Sharpen Up To setting, 118–119
 - sharpening images
 - cautions for, 120
 - after descreening, 123, 124
 - for line art, 140
 - need for, 114–115, 114–115
 - unsharp masks in, 115–119
 - Show Lightest And Darkest Points tool, 67–68, 68
 - simple line art
 - color, 141–143, 142–143
 - scanning, 135–136, 136
 - single-channel histograms, 72–73, 72–73
 - 6-color matrix sets, 97
 - 16 Bit Grayscale setting, 48
 - 16 Bit HDR Grayscale setting, 48
 - size of scanned images, 174
 - skin tone, 91–92, 92
 - Small Computer System Interface (SCSI) cables, 32–33
 - smoothing process, descreening as, 121
 - Snap Album Thumbnails to Grid option, 188
 - specular highlights, 5
 - SRD (smart removal of defects) tool, 126–127, 127
 - expert options for, 130, 131
 - masks for, 129–130, 130
 - preview for, 128
 - saving settings for, 131
 - SRD dialog for, 128–129, 129
 - sRGB profile, 169
 - Standard auto-adjustment tool, 46
 - standard histogram mode, 66
 - status of jobs, 158
 - stopping jobs, 157
 - subtractive color, 15–16, 15–16
 - sweet spot, 29
 - system requirements, 32–33
-
- T**
- targets, calibration, 34, 43–45, 43, 45
 - text files, exporting data to, 112
 - 32-bit CMYK color (four-channel) images, 7, 7
 - three-channel (24-bit RGB color) images, 6, 7
 - three-quarter tone areas, 4, 4
 - Threshold setting
 - for GANE, 125–126
 - for USMs, 117
 - thumbnail sheets, printing, 190
 - TIFF file format, 19–20
 - tonal areas, 4–5, 4

tonal range, color balance across,
81–82, 82

tone compression data in Expert
Dialog, 108, 109

tracking numbers, densitometer
points for, 90, 90

TWAIN technology, 166

12-color matrix sets, 97

24-bit RGB color (three-channel)
images, 6, 7

unsharp masks (USMs), 115

- auto, 115–116
- after descreening, 123, 124
- expert controls for, 118–119,
118–119
- for line art, 140
- manual, 116–118, 116

USB (Universal Serial Bus) cables,
32–33

Use Unsharp Masking option, 123

User Defined option, 53

using albums, 188

version numbers, verifying, 33–34

Virtual Light Tables (VLTs), 182,
187, 187

U

Units of Measure setting, 60

Universal Serial Bus (USB) cables,
32–33

vector images

- vs. bitmap, 2–4, 2–3
- in line art, 134, 134

V

zoom lenses, 29

Zoom tool, 62–64

W

Web, sharpening images for, 120

Windows system requirements, 32

workflows in color management,
174, 175

workspace, 34–36, 35–36

World Wide Web use, 176

Z